

PISTOL GRIP NUTRUNNERS

Torque control with integrated Multi Torque Selector

LTP51 Multi Torque

Bolt capacity M14 – M42

- The Multi Torque Selector makes it possible to preset up to four different shut off levels.
- The Rotary dial mounted on the tool allows the operator to select different torque levels without changing the tool.
- Ideal for situations where:
 - Several different assembly operations take place.
 - Multi-stage tightening operations are required.
 - Several different torque settings are needed.

LTP61 Multi Torque

Bolt capacity M12 – M42

Like the LTP51, the LTP61 is also available in a Multi Torque version.

All features of the LTP51 also apply to the LTP61.

In addition you get a tool that has twice the rundown speed.

Another feature is the reverse function that has fixed positions for both forward and reverse.



Model	Bolt size mm	Square drive in	Torque range at 5 bar		Min torque at 3 bar		Max torque at 6.3 bar		Free speed r/min	Weight ^a kg	Weight ^a lb	Length mm	CS distance mm	Air consumption at free speed		Air inlet thread in	Spline type	Ordering No.
			Nm	ft lb	Nm	ft lb	Nm	ft lb						l/s	cfm			
LTP51 HR008-13-MT	M14	1/2	85 - 150	60 - 110	70	50	175	130	550	3.0	6.6	238	30	19	40	3/8	3	8431 0518 15
LTP51 HR004-20-MT	M18	3/4	200 - 270	145 - 200	145	105	320	235	255	3.9	8.6	275	34	19	40	3/8	4	8431 0518 31
LTP51 HR002-20-MT	M20	3/4	265 - 380	195 - 280	220	160	460	235	175	3.9	8.6	275	34	19	40	3/8	4	8431 0518 49
LTP51 HR001-25-MT	M24	1	450 - 700	330 - 510	300	220	900	660	100	4.3	9.5	305	34	19	40	3/8	5	8431 0518 21
LTP51 HR001-25-MT-FR	M24	1	450 - 700	330 - 510	300	220	900	660	100	4.3	9.5	305	34	19	40	3/8	5	8431 0518 22
LTP51 PHR0005-25-MT	M27	1	595 - 805	435 - 590	450	330	950	695	50	4.3	9.5	305	34	19	40	3/8	5	8431 0518 39
LTP51 HR0007-25-MT	M30	1	740 - 1100	545 - 810	700	516	1500	1106	55	6.6	14.6	345	42	19	40	3/8	9	8431 0518 53
LTP51 HR0005-38-MT	M30	1 1/2	1000 - 1500	720 - 1080	800	590	2000	1500	52	13.8	30	380	68	19	40	3/8	8	8431 0518 55
LTP51 HR0004-38-MT	M36	1 1/2	1500 - 2200	1080 - 1584	1200	890	3000	2200	36	13.8	30	380	68	19	40	3/8	8	8431 0518 58
LTP51 HR0003-38-MT	M42	1 1/2	2000 - 3000	1440 - 2160	1600	1200	4100	3000	26	13.8	30	380	68	19	40	3/8	8	8431 0518 60

FR – Fixed reverse

Model	Bolt size mm	Square drive in	Torque range at 6.3 bar		Min torque at 3 bar		Free speed r/min	Weight ^a kg	Weight ^a lb	Length mm	CS distance mm	Air consumption at free speed		Air inlet thread in	Spline type	Ordering No.
			Nm	ft lb	Nm	ft lb						l/s	cfm			
LTP61 HR100-13-MT	M12	1/2	55 - 100	40 - 75	45	35	1800	3.3	7.3	288	30	20	42	3/8	3	8431 0806 02
LTP61 HR170-13-MT	M14	1/2	95 - 170	70 - 125	70	50	1100	3.3	7.3	288	30	20	42	3/8	3	8431 0806 09
LTP61 HR230-19-MT	M16	3/4	125 - 230	90 - 170	85	60	820	3.3	7.3	288	34	20	42	3/8	4	8431 0806 16
LTP61 HR350-20-MT	M18	3/4	190 - 350	140 - 255	145	105	520	4.2	9.2	325	34	20	42	3/8	4	8431 0806 23
LTP61 HR500-20-MT	M20	3/4	275 - 500	200 - 370	220	160	360	4.2	9.2	325	34	20	42	3/8	4	8431 0806 30
LTP61 HR700-25-MT	M22	1	360 - 650	265 - 480	280	207	280	4.8	10.6	355	34	20	42	3/8	5	8431 0806 33
LTP61 HR900-25-MT	M24	1	480 - 870	350 - 640	300	220	210	4.8	10.6	355	34	20	42	3/8	5	8431 0806 37
LTP61 HR1500-25-MT	M30	1	850 - 1500	625 - 1100	700	516	115	7.1	15.6	395	42	20	42	3/8	9	8431 0806 44
LTP61 HR1900-38-MT	M30	1 1/2	1050 - 1900	770 - 1400	800	576	90	14.4	31.7	430	68	20	42	3/8	8	8431 0806 51
LTP61 HR2800-38-MT	M36	1 1/2	1550 - 2800	1140 - 2060	1200	864	65	14.4	31.7	430	68	20	42	3/8	8	8431 0806 58
LTP61 HR3800-38-MT	M42	1 1/2	2100 - 3800	1540 - 2790	1600	1152	50	14.4	31.7	430	68	20	42	3/8	8	8431 0806 65

^a Without reaction bar.

ACCESSORIES INCLUDED

LTP51/61: Swivel type reaction bar

OPTIONAL ACCESSORIES

Page 67-68



SELECTED SERVICE KITS

Page 68